Built to seal. Made to last.

PRODUCT DATA SHEET

Fullproof® NUCLEAN

TILE SURFACE CLEANER

DESCRIPTION

Fullproof Nuclean is a combination of of acid based material, dispersing agents & is supplied as a light yellow colored solution.

USES

- Removal of mortar, plaster runs, droppings, stains from tile surface.
- Etching of tile surface.
- Tile / Stone works.

ADVANTAGES / CHARACTERISTICS

- Rapid action
- Prolong life of tiles
- Makes good adhesion between tile substrate & tile adhesive both
- Ease in application

TECHNICAL INFORMATION

Properties	Specification
Appearance	Light Yellow
Specific Gravity	1.05 to 1.10
Weathering Resistance	Yes
pH	<1
Chemical Resistance	Yes

APPLICATION PROCEDURE

- Small trial area should be cleaned with Fullproof Nuclean should be selected & rubbed.
- After getting the result proceed the same process.

COVERAGE

Coverage depends an type of stain, surface porosity & dilution of Nuclean

NUCLEAN (Tile Surface Cleaner)

PACKAGING

Nuclean is 500g, 1kg, 5kg, 20kg.

STORAGE & SHELF LIFE

12 months in unopened packs stored at room temperature i.e. 27°C, the liquid component must not be allowed to freeze.

FIRE

Fullproof Nuclean is non-flamable

LIMITATION OF LIABILITY

The data provided is based on tests and intended for guidance only. It is the user's responsibility to ensure suitability for application. Fullproof Coatings is not liable for substrate conditions or application practices. Ensure this sheet is current before use.

COMPANY STANDARD COMPLIANCE

PM GAPAT PVT. LTD.
507, Prisha Apts, Rabale,
Navi Mumbai - 400 701
Mob : +91 9930789393
Mail : info@fullproof.co.in
www.fullproof.co.in

DISCLAIMER: The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results, arising from the use of our products